SMOKE ALARM REQUIREMENTS BASED UPON DATE OF CONSTRUCTION

Date Constructed:	Type of Detector:	Location of Detector:
Built Prior to 7/1/1975	Battery or Electric (hardwired)	Outside each sleeping area (hallway)
Built 7/1/1975 - 1/1/1989	Electric (hardwired)	Outside each sleeping area (hallway)
Built 1/1/1989 - 7/1/1990	Electric (hardwired) and interconnected	Outside each sleeping area (hallway) and on every level
		(including basement; excluding attic)
7/1/1990 – 7/1/1994	Electric (hardwired) and interconnected with battery	Outside each sleeping area (hallway) and on every level
	backup	(including basement; excluding attic)
7/1/1994 – 7/1/2013	Electric (hardwired) and interconnected with battery	Inside and Outside each sleeping area (hallway) and on every
	backup	level (including basement; excluding attic and unoccupied
		spaces)
7/1/2013 and After	Electric (hardwired) and interconnected with battery	Inside and Outside each sleeping area (hallway) and on every
	backup	level (including basement; excluding attic and unoccupied
**		spaces)
**7/1/2013 State Law Update	By 1/1/2018, any prior installed battery operated	
	smoke alarm, supplemental or otherwise, must be	
	sealed, tamper resistant units incorporating a	NOTE: What was required at the time of construction must be
	silence/hush button and using long-life sealed in	maintained. Electric (hardwired) detectors cannot be replaced
	batteries.	with long-life sealed in battery detectors. All detectors must
		be replaced if 10 years old or more.
	This law update affects battery operated smoke	
	alarms only. It does not affect hardwired alarms.	Requirements for smoke detectors inside bedrooms when not
	ALL ALARMS MUST BE REPLACED IF THE UNIT IS 10	required at time of construction is a local ordinance and
	YEARS OLD OR MORE.	required if a rental license is to be obtained.

12.13.13 Smoke Detector Requirements by Construction Date